



UM12-1172271

UM12

ULTRASONIC SENSORS

SICK
Sensor Intelligence.



Ordering information

| Type | Part no. |
|--------------|----------|
| UM12-1172271 | 6053545 |

Other models and accessories → www.sick.com/UM12



Detailed technical data

Mechanics/electronics

| | |
|--|---|
| Supply voltage V_s | DC 15 V ... 30 V ¹⁾ |
| Power consumption | $\leq 0.9 \text{ W}$ ²⁾ |
| Initialization time | < 300 ms |
| Design | Cylindrical |
| Housing material | Metal (nickel-plated brass, PBT) Ultrasonic transducer: polyurethane foam, glass epoxy resin |
| Thread size | M12 x 1 |
| Connection type | Male connector, M12, 4-pin |
| Indication | 2 x LED |
| Weight | 15 g |
| Sending axis | Straight |
| Dimensions (W x H x D) | 12 mm x 12 mm x 60.1 mm |
| Enclosure rating | IP65 / IP67 |
| Protection class | III |

¹⁾ Limit values, reverse-polarity protected Operation in short-circuit protected network: max. 8 A, class 2.

²⁾ Without load.

Performance

| | |
|--|-----------------------------|
| Operating range, limiting range | 20 mm ... 150 mm, 250 mm |
| Target | Natural objects |
| Resolution | $\geq 0.069 \text{ mm}$ |
| Repeatability | $\pm 0.15 \%$ ¹⁾ |
| Accuracy | $\pm 1 \%$ ²⁾ |
| Temperature compensation | ✓ |
| Response time | 24 ms ³⁾ |
| Output time | 8 ms |

¹⁾ In relation to the current measured value, minimum value \geq resolution.

²⁾ Referring to current measurement value.

³⁾ Subsequent smoothing of the analog output, depending on the application, may increase the response time by up to 200 %.

⁴⁾ Functions may vary depending on sensor type.

| | |
|---------------------------------------|---|
| Ultrasonic frequency (typical) | 380 kHz |
| Additional function | Teach-in of analog output, Invertable analog output, reset to factory default 4) |

1) In relation to the current measured value, minimum value \geq resolution.

2) Referring to current measurement value.

3) Subsequent smoothing of the analog output, depending on the application, may increase the response time by up to 200 %.

4) Functions may vary depending on sensor type.

Interfaces

| | |
|----------------------|-------------------------------------|
| Analog output | |
| Number | 1 |
| Type | Voltage output |
| Voltage | 0 V ... 10 V, $\geq 100,000 \Omega$ |
| Resolution | 12 bit |

Ambient data


| | |
|---------------------------------------|-------------------|
| Ambient temperature, operation | -25 °C ... +70 °C |
| Ambient temperature, storage | -40 °C ... +85 °C |

Classifications

| | |
|-----------------------|----------|
| ECI@ss 5.0 | 27270804 |
| ECI@ss 5.1.4 | 27270804 |
| ECI@ss 6.0 | 27270804 |
| ECI@ss 6.2 | 27270804 |
| ECI@ss 7.0 | 27270804 |
| ECI@ss 8.0 | 27270804 |
| ECI@ss 8.1 | 27270804 |
| ECI@ss 9.0 | 27270804 |
| ECI@ss 10.0 | 27270804 |
| ECI@ss 11.0 | 27270804 |
| ETIM 5.0 | EC001846 |
| ETIM 6.0 | EC001846 |
| ETIM 7.0 | EC001846 |
| ETIM 8.0 | EC001846 |
| UNSPSC 16.0901 | 41111960 |


Dimensional drawing (Dimensions in mm (inch))

UM12-11x2261, UM12-11x2271




- ① Connection
- ② Mounting nuts, SW 17 mm
- ③ Status display supply voltage active (green), switching and analog output (orange)

Connection type




Connection diagram

UM12-11x2261, UM12-11x2271



Detection area



UM1x-x17



- ① Detection range dependent on reflection properties, size, and alignment of the object
- ② Limiting range
- ③ Operating range
- ④ Example object: aligned plate 500 mm x 500 mm
- ⑤ Example object: cylindrical bar with a diameter of 10 mm

Recommended accessories

Other models and accessories → www.sick.com/UM12

| | Brief description | Type | Part no. |
|---|---|--------------------|----------|
| Mounting brackets and plates | | | |
|  | Mounting plate for M12 sensors, steel, zinc coated, without mounting hardware | BEF-WG-M12 | 5321869 |
| Plug connectors and cables | | | |
|  | Head A: female connector, M12, 4-pin, straight, A-coded Head B: Flying leads Cable: Sensor/actuator cable, PVC, unshielded, 2 m | YF2A14-020VB3XLEAX | 2096234 |

Recommended services

Additional services → www.sick.com/UM12

| | Type | Part no. |
|--|--|----------|
| Warranty extensions | | |
| <ul style="list-style-type: none">• Product area: Identification solutions, machine vision, Distance sensors, Detection and ranging solutions• Range of services: The services correspond to the scope of the statutory manufacturer warranty (SICK general terms and conditions of purchase)• Duration: Five-year warranty from delivery date. | Extended warranty for a total of five years from delivery date | 1680671 |

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com