

# Product datasheet

Specifications



inductive sensor XS1 M8 - L42mm  
- brass - Sn1.5mm - 12..24VDC -  
cable 5m

XS108BLPAL5

## Main

|                               |  |
|-------------------------------|--|
| Range of product              | Telemecanique Inductive proximity sensors XS         |
| Series name                   | General purpose                                      |
| Sensor type                   | Inductive proximity sensor                           |
| Sensor name                   | XS1  |
| Sensor design                 | Cylindrical M8                                       |
| Size                          | 42 mm  |
| Body type                     | Fixed  |
| Enclosure material            | Nickel plated brass                                  |
| Type of output signal         | Discrete   |
| Wiring technique              | 3-wire   |
| [Sn] nominal sensing distance | 1.5 mm   |
| Discrete output function      | 1 NO   |
| Discrete output type          | PNP  |
| Electrical connection         | Cable  |
| Cable length                  | 5 m  |
| [Us] rated supply voltage     | 12...24 V DC with reverse polarity protection        |
| Switching capacity in mA      | <= 200 mA with overload and short-circuit protection |
| IP degree of protection       | IP67 conforming to IEC 60529                         |

## Complementary

|                                    |                 |
|------------------------------------|-----------------|
| ISO thread                         | M8 x 1          |
| Detection face                     | Frontal         |
| Detector flush mounting acceptance | Flush mountable |
| Material                           | Metal           |
| Front material                     | PPS             |
| Operating zone                     | 0...1.2 mm      |
| Differential travel                | 1...15% of Sr   |
| Output circuit type                | DC              |

|                                 |                              |
|---------------------------------|------------------------------|
| <b>Cable composition</b>        | 3 x 0.11 mm <sup>2</sup>     |
| <b>Wire insulation material</b> | PVC                          |
| <b>Status LED</b>               | Output state: 1 LED (yellow) |
| <b>Supply voltage limits</b>    | 10...36 V DC                 |
| <b>Switching frequency</b>      | <= 1000 Hz                   |
| <b>Maximum voltage drop</b>     | <2 V (closed)                |
| <b>Current consumption</b>      | <= 10 mA no-load             |
| <b>Maximum delay first up</b>   | 15 ms                        |
| <b>Maximum delay response</b>   | 5 ms                         |
| <b>Maximum delay recovery</b>   | 0.3 ms                       |
| <b>Marking</b>                  | CE                           |
| <b>Threaded length</b>          | 33 mm                        |
| <b>Length</b>                   | 42 mm                        |
| <b>Net weight</b>               | 0.155 kg                     |

## Environment

|  |   |
|--|---|
| <b>Product certifications</b>                | CSA<br>UL   |
| <b>Ambient air temperature for operation</b> | -25...70 °C   |
| <b>Ambient air temperature for storage</b>   | -40...85 °C   |
| <b>Vibration resistance</b>                  | 25 gn amplitude = +/- 2 mm (f = 10...55 Hz) conforming to IEC 60068-2-6 |
| <b>Shock resistance</b>                      | 50 gn for 11 ms conforming to IEC 60068-2-27                            |

## Packing Units

|                                     |          |
|-------------------------------------|----------|
| <b>Unit Type of Package 1</b>       | PCE      |
| <b>Number of Units in Package 1</b> | 1        |
| <b>Package 1 Weight</b>             | 111.0 g  |
| <b>Package 1 Height</b>             | 6.6 cm   |
| <b>Package 1 width</b>              | 9.5 cm   |
| <b>Package 1 Length</b>             | 13 cm    |
| <b>Unit Type of Package 2</b>       | S02      |
| <b>Number of Units in Package 2</b> | 10       |
| <b>Package 2 Weight</b>             | 1.699 kg |
| <b>Package 2 Height</b>             | 15 cm    |
| <b>Package 2 width</b>              | 30 cm    |
| <b>Package 2 Length</b>             | 40 cm    |
| <b>Unit Type of Package 3</b>       | PAL      |
| <b>Number of Units in Package 3</b> | 160      |
| <b>Package 3 Weight</b>             | 17.76 kg |
| <b>Package 3 Height</b>             | 60 cm    |
| <b>Package 3 width</b>              | 80 cm    |
| <b>Package 3 Length</b>             | 160 cm   |

## Offer Sustainability

---

|                                   |   |
|-----------------------------------|---|
| <b>Sustainable offer status</b>   | Green Premium product   |
| <b>REACH Regulation</b>           | <a href="#">REACH Declaration</a>   |
| <b>EU RoHS Directive</b>          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a> |
| <b>Mercury free</b>               | Yes   |
| <b>RoHS exemption information</b> | Yes   |
| <b>Environmental Disclosure</b>   | <a href="#">Product Environmental Profile</a>   |
| <b>Circularity Profile</b>        | <a href="#">End of Life Information</a>   |

---

## Contractual warranty

---

|                 |           |
|-----------------|-----------|
| <b>Warranty</b> | 18 months |
|-----------------|-----------|

---